



15" Bezel Free Fanless POS terminal

- 15" True Flat PCAP touch screen with stylish & durable Aluminum chassis with fanless heat elimination
- Compatible with different card reader Magnetic card reader (MSR) / I-Button / RFID
- Compatible with different customer display VFD customer display / 9,7" LED Monitor
- HDD or optional SSD storage option
- Big and Stable Stand



| | | |
|--|---|-------------------------|
| Model | AADPOS2 | |
| Color | Black/White | |
| System | | |
| Chipset | Intel Bay Trail-D J1900 | |
| CPU | Intel J1900 Quad-Core 2.0GHz Fanless | |
| Memory | 4GB DDRIII , 1 x DDRIII 1333 DIMM, up to 8GB | |
| Storage | 64GB 2.5" SSD, 1 x 2.5" SATA and 1 x mSATA, up to 2TB | |
| Front Display | | |
| Panel | 15" TFT LED | |
| Resolution | 1024x768 | |
| Touch Screen | Projected capacitive touch | |
| Touch Screen Interface | USB | |
| I/O PORTS | 1 x DB-15 VGA | 1 x Line in |
| | 1 x HDMI | 1 x Audio out |
| | 3 x RJ-45 COM1&2&3 | 1 x 12V DC in |
| | 2 x USB 3.0 | 1 x Reset Switch |
| | 2 x USB 2.0 | 1 x Power On/Off Switch |
| | 1 x LAN | |
| Options | 1*2*3 Magnetic Stripe Reader, VFD , 9.7" Second Display , WiFi, iButton, RFID | |
| Environmental | | |
| Operating / Storage Humidity | 20% - 80% / 20% - 80% | |
| Operating / Storage Temperature | 0°C - 40°C / -20°C - 60°C | |
| Power Consumption | 72W (max.) | |
| Accessories In Packing | 12V/7A Power Adapter | |
| | Power Cable (various plugs) | |
| | Driver Disk | |
| | 3 x RJ45 to DB-9 Serial Cables | |