



- Compatible with different touch screen
5-wire resistive touch / True-flat capacitive touch / Infrared touch
- Compatible with different card reader
Magnetic card reader (MSR) /I-Button
- Compatible with different customer display
VFD customer display / 8" LED Monitor
- Compatible with different I/O ports
- Compatible with different processor
- Fan or non-Fan
- Big and Stable Stand





System		
Chipset	Intel Bay Trail-D J1900	Intel NM70
CPU	Intel J1900 Quad-Core 2.0GHz, 2M Fanless/10W	Intel 1037U Dual-Core 1.8GHz, 3M Cache 17W
Memory	2GB DDRIII , 1 x DDRIII 1333 DIMM, up to 4GB	
Storage	MSATA32/64/128GB SSD or 2.5" SATA 500GB HDD	
Ethernet Card	Realtek 8103EL 10/100M Support diskless boot	
Front Display		
Panel	15" TFT LED	
Brightness/Contrast	450 cd/m ² / 700 : 1	
Resolution	1024x768	
Touch Screen	5-wire resistive touch / True-flat capacitive touch / Infrared touch	
I/O PORTS		
Serial/Parallel Port	1x Serial; 1x Parallel	2xSerial
USB	4 x USB 2.0	
LAN	1 x RJ45 10/100/1000M	
Audio Jack	1 x Mic in & SPK out	
Support OS		
Windows / Linux	Windows XP, POS Ready 2009, Windows 7/8/10, POS Ready 7, Unbuntu 13.04 LTS	
Optional Accessoires		
Card Reader	1&2&3 Magnetic Stripe Reader, RFID, I-Button	
Customer Display	LED/VFD	
2 nd Display	8"/10,4" LED Monitor	
Wireless Module	802.11 a/b/g/n	
Fingerprint Scanners	optional	
Environmental		
Operating / Storage Humidity	20% - 80% / 20% - 80%	
Operating / Storage Temperature	0°C - 40°C / -20°C - 60°C	
Power Consumption	60W (max.)	
Packing Information		
Carton Size	500x300x470mm	
Net / Gross Weight	6,5KG / 6,8KG	